


## Declaration of performance no. 9970.000200 BauPVo2013-07-14

	Mechanical lock according to DIN EN 12209 for fire-proof doors and/or smoke control doors
Unique identification code of the product type:	



3. Intended use as designed by the manufacturer or intended uses of the construction product according to the applicable harmonised technical specification:

The lock ensures the proper locking of the door, also if it is a fire-proof and/or smoke control door, and is locked with a suitable door closer.

4. Name, registered trade name or registered brand, and contact address of the manufacturer according to Article 11 paragraph 5, CPR:

Beyer & Müller GmbH & Co.KG, Am Lindenkamp 55, 42549 Velbert

Website: www.beyer-und-mueller.de

5. Name and contact address of the authorised representative where applicable, who is assigned the tasks according to Article 12 paragraph 2:

## not named

6. System or systems for assessing and checking the performance reliability of the construction product according to Attachment V CPR:

## System 1

- 7. The test laboratory no. 0432 of the Materials Testing Office North Rhine-Westphalia (MPA NRW) performed the type test and issued the certificate of conformity **0432-CPR-0008 2-03**.
- 8. European Technical Assessment

not performed

12/01/2021 Page **1** of **3** 



Declared performance according to certification key of the respective lock:
(The certification key can be found in the certificate of conformity on our website or on the sticker on the top of the lock.)

Utilisation category	1st position
Durability	2nd position
Door mass and closing force	3rd position
Suitability for usage at fire-proof and smoke control doors	4th position
Safety	5th position
Corrosion resistance and temperature	6th position
Protective effect and drill resistance	7th position
Field of door usage	8th position
Type of key operation	9th position
Type of spindle operation	10th position
Key identification	11th position

Harmonised technical specifications: DIN EN 12209:2004-3

Essential characteristics	Performance:
1. Utilisation category	Class 3: high probability of misuse e.g. doors in public buildings
2. Durability	Class L: 100,000 test cycles; load of 25 N on the latch
	Class M:200,000 test cycles; load of 25 N on the latch
3. Door mass and closing force	Class 5: door mass up to 200 kg; max. 25 N closing force
Suitability for usage at fire-proof and smoke control doors	Class 1: suitable for usage at fire-proof/smoke control doors
5. Safety	according to standard only Class 0: no safety requirements
6. Corrosion resistance and temperature	Class F: high corrosion resistance; temperature requirement -20 to 80 °C
7. Protective effect and drill resistance	Class 0: no evident protective effect
	Class 1: medium protective effect; no drill resistance
	Class 4: high protective effect; no drill resistance
	Class 6: very high protective effect; no drill resistance
8. Field of door usage	Class B
9. Type of key operation and locking	Class A: cylinder lock; manual locking
	Class C: cylinder lock; manual locking with interlocking

12/01/2021 Page **2** of **3** 



	device
	Class H: lock without key operation; automatic locking
10. Type of spindle operation	Class 0: lock without follower
	Class 2: lock for operation of a handle without supporting spring
11. Key identification	Class 0: no requirements
Hazardous substances	The materials in this product do not contain any hazardous substances. Also, they do not release any substances into the environment to a higher extent than specified in any European standard or regulation.

10. The product described under sections 1 and 2 fulfils the performance characteristics listed under section 9.

According to number 4, the manufacturer is solely responsible for the creation of this declaration of performance. Signed for or on behalf of the manufacturer by:

Dipl.-Wirtsch. - Ing. Matthias Kohl / Managing Director

(Name of the signatory and function at the company)

Velbert, 12/01/2021

(Place and date of the first issue)

(Signature)

12/01/2021 Page 3 of 3

Marthins Ko